



### HARDO Ortholine

- Speziell entwickelt für die Orthopädie-Schuhtechnik zum Anschluss an externe Filteranlagen
- Absaugwand extrem weit zurückgesetzt
- Automatische Bandspannung

### HARDO Ortholine

- Specially designed for orthopaedic shoe technology and suitable for connection to external filter plants
- Suction wall extremely standing back
- Automatic belt tension



## HARDO ORTHOLINE 150 B

Art. 100489

- Orthopädie Fräs- und Schleifmaschine
- Zwillingsfräse (B-Fräse = Absatz- und Sohlenfräser)
- Absatzfrontkegel auf Bajonettverschluss
- Schleifbänder 2x 40 x Ø 175 mm + 1x 100 x Ø 100 mm
- Klappenbetätigung am jeweiligen Antrieb gekoppelt
- Einzelantrieb des Breitbandes
- Schleifarmatur auf Bajonettverschluss
- Bimser multiverstellbar
- Doppeldrucktaster
- Ergonomisches HARDO Design
- Farbe: hellgrau RAL 7035
- Elektr. Daten: 400V/3Ph/50Hz/3,2kW
- Maße: 1500 x 780 x 1855 mm (BxTxH)
- Gewicht: 410 kg

Änderungen vorbehalten 01/20

- Orthopaedic trimming- and sanding machine
- Twin trimmers (B-version = heel- and sole-trimmer)
- Heel breaster on bajonet
- Sanding belts 2x 40 x Ø 175 mm + 1x 100 x Ø 100 mm
- Flap activation connected to the respective drive
- Separate control of right belt
- Sanding wheel on bajonet
- Naumkeag multi-adjustable
- Button panel
- Ergonomic HARDO Design
- Colour: light grey RAL 7035
- Electr. specifications: 400V/3Ph/50Hz/3,2kW
- Dimensions: 1500 x 780 x 1855 mm (wx dxh)
- Weight: 410 kg

Modifications reserved 01/20