



HARDO IDEAL UNIT 165 B

Art. 100779

Kombination von Ausputzmaschine und Presse

HARDO IDEAL Combi 115 B

- Kombinierte Ausputzmaschine
- Integriertes Absaugsystem mit Baumwollfilter
- Schräge Absaugwand
- Zwillingsfräse (B-Fräse = Absatz- und Sohlenfräser)
- Absatzfrontkegel auf Bajonettverschluss
- Schleifbänder 2 x 40 x Ø175 mm
- Schleifbandspannung manuell
- Revolverpolierabteilung mit 6 Armaturen
- Bimser, schwenkbar

HARDO Schnellpresse Standard:

- Sicherheitsschaltung
- V-Druckbügel mit 12 Paar Innendruckplatten
- Schiebevorrichtung mit Sohlenkissen und Absatzdruckstück
- Kompressoranlage
- Farbe: lichtgrau RAL 7035
- Elektr. Daten: 400V/3Ph/50Hz/4,1 kW
- Maße: 1650 x 780 x 1880 mm (BxTxH)
- Gewicht: 520 kg

Änderungen vorbehalten 06/20

Combination of finisher and press

HARDO IDEAL Combi 115 B

- Combined finisher
- Integrated extraction system with cotton filter
- Diagonal suction wall
- Twin trimmers (B-version = heel- and sole-trimmer)
- Heel breaster on bajonet
- Sanding belts 2 x 40 x Ø175 mm
- Belt tension manual
- 6 Polishing tools on rotating shafts
- Naumkeag, swiveling

HARDO rapid press Standard:

- Safety control unit
- V-arm incl. 12 pairs lasts
- Sliding device with sole cushion and heel press piece
- Compressor unit
- Colour: light grey RAL 7035
- Electr. specifications: 400V/3Ph/50Hz/4,1 kW
- Dimensions: 1650 x 780 x 1880 mm (wxdxh)
- Weight: 520 kg

Modifications reserved 06/20