





# HARDO FILTER CABINET FS-4P

- External extraction system
- Automatic performance regulation for continuous optimal dust suction
- Decompression process
- High-performance exhauster
- Integrated sound absorber
- Automated filter cleaning system
- Easily removable dust container
- Right-side mounted switch cabinet
- Left-sided pipe connection

## Optional for an additional charge:

- Control box mounted on the left, inflow air-box on the right
- Integrated silencer, for particularly quiet running (+15kg)
- Front lower door

# **Technical data:**

- Air performance 2000 m<sup>3</sup>/h
- Filter area 10.8 m²
- Colour: light-grey RAL 7035
- Measurements:  $1400 \times 850 \times 2000 \text{ mm (BxTxH)}$
- Weight: 359 kg

## Electrical data:

- Electrical voltage 400 V/ 3 Ph +N+ PE / 50/60 Hz
- Power rating: 2.2 kW

Modifications reserved 01/23





# HARDO FILTER CABINET FS-8P

- External extraction system
- Automatic performance regulation for continuous optimal dust suction
- Decompression process
- High-performance exhauster
- Integrated sound absorber
- Automated filter cleaning system
- Easily removable dust container
- Right-side mounted switch cabinet
- Left-sided pipe connection

## Optional for an additional charge:

- Control box mounted on the left, inflow air-box on the right
- Integrated silencer, for particularly quiet running (+15kg)
- Front lower doors

# **Technical data:**

- Air performance 4000 m<sup>3</sup>/h
- Filter area 21.6 m²
- Colour: light-grey RAL 7035
- Measurements:  $2195 \times 850 \times 2000 \text{ mm (BxTxH)}$
- Weight: 625 kg

## Electrical data:

- Electrical voltage 400 V/ 3 Ph +N+ PE / 50/60 Hz
- Power rating: 4.4 kW

Modifications reserved 01/23

41





# HARDO FILTER CABINET FS-12P

- External extraction system
- Automatic performance regulation for continuous optimal dust suction
- Decompression process
- High-performance exhauster
- Integrated sound absorber
- Automated filter cleaning system
- Easily removable dust container
- Right-side mounted switch cabinet
- Left-sided pipe connection

## Optional for an additional charge:

- Control box mounted on the left, inflow air-box on the right
- Integrated silencer, for particularly quiet running (+15kg)
- Front lower doors

# Technical data:

- Air performance 6000 m<sup>3</sup>/h
- Filter area 32.6 m²
- Colour: light-grey RAL 7035
- Measurements:  $2990 \times 850 \times 2000 \text{ mm (B}\times\text{T}\times\text{H)}$
- Weight: 889 kg

## Electrical data:

- Electrical voltage 400 V/ 3 Ph +N+ PE / 50/60 Hz
- Power rating: 6.6 kW

Modifications reserved 01/23